

OPTIKA[®]

M I C R O S C O P E S
I T A L Y



B-290 Series

Educational & Routine Lab Upright Microscopes

Best Value-for-Money Solution and Versatile Use

SUITABLE FOR TEACHERS, EXPERTS & ROUTINE LAB

- » One of the most flexible microscopes in the world
- » For secondary school, higher education and laboratories
- » Ideal for education, biology, histology

PRICE/PERFORMANCE RATIO

- » Binocular and trinocular heads with 20mm field number
- » E-PLAN objectives for high numerical apertures and flat images
- » Convenient, rackless moving stage to prevent scrapes



B-290TB - A Completely New, Revolutionary Experience

BREAK NEW GROUND WITH TABLET PC

- » Get accurate, dependable results in one click
- » Equipped with the most reliable OS, Windows 10
- » Holding solution for open discussion, 360° rotating and tilting

OPTIMUM AND UNPARALLELED COMFORT IN USE

- » Large touch screen of 10.1" with fast, responsive and smooth control
- » Easily detachable, can be used as a laptop (keyboard included)
- » Simultaneous camera and power connection for long-term operation






X-LED³ - Exclusive Lighting Source

POWERFUL AND UNIFORM ILLUMINATION

- » Unmatched colour fidelity and brightness of your specimen
- » Special technology, able to double the light intensity
- » Constant pure-white colour temperature (6.300K)

CUT ELECTRICITY BILLS BY 90%

- » Money & energy saving
- » Low power consumption, only 3.6W
- » LED long lifetime (50.000 hours = 20 years at 8 hours/day usage)



IOS - Infinity Optical System

LABORATORY GRADE OPTICS

- » Planachromatic optics with more than 90% flat field
- » Optimum quality on 20mm field (E-PLAN)
- » True infinity optical system

A COMPLETE SYSTEM

- » Optional 20x and 60x objectives available
- » Use the polarizing set without any distortion of the final image
- » Fully centerable condenser for precise light control



Icons



Binocular



Trinocular



Inclined head



Field number



Rotating head 360°



Infinity-corrected optics



Max. magnification



Anti-fungus treatment



Transmitted light



Polarized light



X-LED illuminator



USB connection



Tablet screen size



Camera resolution



Software included



HDMI Output



MicroSD card



Bluetooth

B-290 Series

X-LED³ Exclusive Lighting Source

Special technology able to double the light intensity for incomparable performance, ensuring constant pure-white colour temperature (6.300K colour temperature).

Relevant money and energy saving thanks to the incredibly low energy consumptions which allows you to cut the electricity bills by 90%!

Safe And Convenient Operations


The rackless stage has been designed with a belt-driven mechanism that allows a smooth movement without any protruding part.

This design gives you a more compact solution and lowers any risk of injury after accidentally hitting the rack with your hands.




Clear Observation With 100x Objective


Students and basic users will enjoy B-290 Series for the clear and sharp images they can get using 100x objective with water, thanks to the extremely bright X-LED³ light source and the fully centerable Abbe condenser. Forget about the tedious lens cleaning you are used to when using 100x objective: dirt and dust will not affect your objective.



100x DRY



100x OIL



100x WATER


Pine, one year stem.

For a professional use, immersion oil is the recommended solution to get the best performance available from any 100x objective.

Educational & Routine Lab Upright Microscopes

Laboratory Grade Optics, E-PLAN & IOS System

OPTIKA E-PLAN objectives ensure bright, clear images with excellent flatness and compensation for chromatic aberration. IOS Infinity-corrected optical system prevents image deterioration even if other optical components are added, such as polarizers, beamsplitters and so on.



Large Specimen View (20mm Field Number)

The **F.O.V.** (field of view) is based on a comfortable diameter of 20mm. This means that a wide area of the sample can be inspected and allows a natural and easy view, particularly needed in a laboratory environment.

Easy Transportation

B-290 has a carefully shaped design that gives stability and ease in the transportation. Thanks to the handle on the back, it can be safely moved around the classroom or the laboratory.

Optimum And Unparalleled Comfort In Use

The B-290TB offers you a unique, incomparable solution, including a built-in camera of 3Mp and a Windows tablet with large touch screen, for a responsive and smooth control. Simultaneous camera and power connection ensure long-term operation, with dependable results in one click. It offers a reliable and comfortable solution for open discussion, with 360° rotating and tilting tablet, easily detachable, that can be used as a laptop.



Get the most out of our accessories



M-666.290 Heating stage

Use the temperature controlled heating stage for specific applications where accurate temperature selection up to 50°C and programmable settings are needed.

Requested in research arenas such as microbiology, biochemistry, material science, pharmacology, crystallographic characterization, surface quality control, and in all the temperature related inspections.

M-184 Darkfield condenser

With optional diaphragm M-184 you can easily obtain a darkfield view for dry objectives. M-184 can be placed directly under the condenser without the need of additional operations.

DARKFIELD CONDENSER





B-290 Series


Applications

Some application examples showing the extreme versatility of B-290 Series. Application in education, biology, botany and simple material analysis, where all the samples are mounted on standard glass slides.

Legend

1. B-290TB with 360° rotating tablet PC for discussion.
2. Pine, one year stem, with B-292 and 10x objective.
3. B-290 Series exclusive X-LED³ illumination system.
4. B-293 used by a teacher.
5. Lilly pollen, with B-292PLi and 20x objective.
6. Ascaris female, with B-293 and 40x objective.
7. Student setting the right focusing on a B-290TB.





B-290 Series - Overview

This series incorporates all the experience gathered by OPTIKA Microscopes in the field of light microscopy, adapted specifically for routine laboratory brightfield applications. These microscopes are suitable for routine microscopy and have an ergonomic design for comfortable long-term use.

All main controls are located close to each other, which enable operation with minimal movements.

Observation mode:

Brightfield, polarized light.

Heads:

B-292 models:

Binocular, 360° rotating and 30° inclined.

B-293 models:

Trinocular, 360° rotating and 30° inclined.

B-290TB:

Digital model, binocular with camera and 10.1" tablet, 360° rotating and 30° inclined.

Interpupillary distance:

B-290TB/B-292 models: Adjustable between 48 and 75 mm.

B-293 model: Adjustable between 55 and 75 mm.

Dioptric adjustment:

On the left eyepiece tube.

Eyepieces:

WF10x/20 mm.

Nosepiece:

Quadruple revolving nosepiece, rotation on ball bearings.

Objectives:

E-PLAN or IOS E-PLAN optical system (on PLi models) with an anti-fungus treatment. Different magnifications available.

Specimen stage:

Double layer rackless mechanical sliding stage, 150x139mm, 75x33mm X-Y movement range. Vernier scale on the two axes, accuracy: 0.1mm.

Focusing:

Coaxial coarse and fine focusing mechanism with limit stop to prevent the contact between objective and specimen.

Adjustable tension of coarse focusing knob.

Condenser:

N.A 1.25, centerable, adjustable height.

Illumination:

X-LED³ type with white 3.6W LED and light intensity control.

Color temperature: 6.300K.



B-290 Series - Range

B-292



Binocular head with E-PLAN objectives, rackless stage and exclusive X-LED³ for unmatched performance, powerful and uniform illumination.

B-292PLi



Binocular head with E-PLAN IOS (infinity corrected) objectives, rackless stage and exclusive X-LED³ for incredibly bright illumination.

B-293



Trinocular head with E-PLAN objectives, rackless stage and exclusive X-LED³ for unmatched performance, powerful and uniform illumination.


B-293PLi



Trinocular head with E-PLAN IOS (infinity corrected) objectives, rackless stage and exclusive X-LED³ for incredibly bright illumination.

B-290 Series - Range

B-290TB



3MP Built-in camera and 10.1" Windows tablet PC with E-PLAN objectives, rackless stage and exclusive X-LED³ for unmatched performance in illumination. Ideal for discussion group with 360° rotating tablet.

B-290 Series - Optical performance

Optical performance B-292, B-293 and B-290TB

Eyeiece			10x (M-160)		15x (M-161)		20x (M-162)	
Field number (mm)			20		16		10	
Objective	N.A.	W.D (mm)	Total magnification	Field of View (mm)	Total magnification	Field of View (mm)	Total magnification	Field of View (mm)
4x (E-PLAN 160 mm)	0.1	15.2	40x	5	60x	4	80x	2.5
10x (E-PLAN 160 mm)	0.25	5.5	100x	2	150x	1.6	200x	1
20x (E-PLAN 160 mm)	0.4	5	200x	1	300x	0.8	400x	0.5
40x (E-PLAN 160 mm)	0.65	0.45	400x	0.5	300x	0.4	800x	0.25
60x (E-PLAN 160 mm)	0.8	0.13	600x	0.33	900x	0.26	1200x	0.16
100x (E-PLAN 160 mm)	1.25 (oil)	0.13	1000x	0.2	1500x	0.16	2000x	0.1

Optical performance B-292PLi and B-293PLi

Eyeiece			10x (M-160)		15x (M-161)		20x (M-162)	
Field number (mm)			20		16		10	
Objective	N.A.	W.D (mm)	Total magnification	Field of View (mm)	Total magnification	Field of View (mm)	Total magnification	Field of View (mm)
4x (E-PLAN IOS)	0.1	16.8	40x	5	60x	4	80x	2.5
10x (E-PLAN IOS)	0.25	5.8	100x	2	150x	1.6	200x	1
20x (E-PLAN IOS)	0.4	5.1	200x	1	300x	0.8	400x	0.5
40x (E-PLAN IOS)	0.65	0.45	400x	0.5	300x	0.4	800x	0.25
60x (E-PLAN IOS)	0.8	0.14	600x	0.33	900x	0.26	1200x	0.16
100x (E-PLAN IOS)	1.25 (oil)	0.13	1000x	0.2	1500x	0.16	2000x	0.1

B-290TB - Digital microscope with camera and tablet

The latest OPTIKA digital microscopes with Windows tablet PC open new microscopy horizons, combining high-end optics with innovative digital technology for microscopic imaging. B-290TB includes a 3MP camera with a 10.1" Windows tablet. View, capture, analyze and share your images with simplicity and reliability.

Detachable

Use it as a laptop PC!

Intel Quad-Core processor, Windows 10.
Battery life up to 10 hours.



PATENTED

Simultaneous Data & Power Feed

Recommended for schools and long operation, as the tablet can be recharged during use.



360° Rotating

Rotating

A special holder allows to easily attach the tablet to the microscope and freely rotate it.



Intuitive, Yet Powerful Software

Simple and user-friendly, ideal for students and experienced users.



B-290TB - Digital microscope with camera and tablet



TABLET TECHNICAL SPECIFICATIONS

Model	Tablet 10.1"
Operating System	Windows 10 32-bit
Language	Multilanguages already installed
Image capturing software	OPTIKA Vision lite
CPU	Intel® Atom™ Z3735F, Quad core
CPU speed	1,83 GHz
Graphics Card	Intel® HD Graphics 3D Accelerator
Memory	Ram 2,048 GB DDR3L
LCD display	LED 10.1" IPS Multi Touch Screen
LCD resolution	1280 x 800, 16/10 (WXGA)
Storage	HDD 32GB
Network	Wireless, Bluetooth 4.0
Input/output ports	Micro USB-B - USB - Microphone - MicroSD card reader - Mini HDMI - Head-phone
Control Buttons	Auto rotate off, volume control
Battery Technology	Lithium-ion battery, 2x cell
Battery capacity	6000 mAh
Max load	18 W
Dimensions	Thickness 10,5 mm, Height 17,4 cm, Width 25,7 cm
Weight	600 g
Cables included	OTG cable (Micro USB-B to USB-A)
Also included	Instruction manual, Keyboard with touchpad, touch pen.

CAMERA TECHNICAL SPECIFICATIONS

Digital camera resolution	3.14 MegaPixels
Signal output	USB 2.0
Sensor Size	1/2.5"
Sensor technology	CMOS
Image format	4\3
Full Image size	2048 x 1536
Pixel size	2.2 x 2.2 micron
Frame rate full resolution	5 frames\sec
Frame rate other resolutions	8 FPS (1280x1024) - 30FPS (640x480)
Automatic White Balance	Auto - Man
Automatic Gain Control	Auto - Man
Automatic Back light control	Auto - Man
Exposure control	Auto - Man


B-290 Series - Comparison chart

Model	Head	Eyepieces	Nosepiece	Objectives	Stage	Focusing	Condenser	Illuminator
B-292	Binocular, 360° rotating, 30° inclined.	Wide Field 10x/20mm	Quadruple, reversed	E-PLAN 4x, 10x, 40x, 100x	Double layer, 150x139 mm with X-Y moving range 75x33mm. Rackless in X direction	Coaxial coarse and fine focusing	Sliding-in, N.A. 1.25 Abbe type with adjustable height and iris diaphragm	3.6W X-LED ³ system with adjustable intensity
B-292PLi	Binocular, 360° rotating, 30° inclined.	Wide Field 10x/20mm	Quadruple, reversed	IOS E-PLAN 4x, 10x, 40x, 100x	Double layer, 150x139 mm with X-Y moving range 75x33mm. Rackless in X direction	Coaxial coarse and fine focusing	Sliding-in, N.A. 1.25 Abbe type with adjustable height and iris diaphragm	3.6W X-LED ³ system with adjustable intensity
B-293	Trinocular, 360° rotating, 30° inclined	Wide Field 10x/20mm	Quadruple, reversed	E-PLAN 4x, 10x, 40x, 100x	Double layer, 150x139 mm with X-Y moving range 75x33mm. Rackless in X direction	Coaxial coarse and fine focusing	Sliding-in, N.A. 1.25 Abbe type with adjustable height and iris diaphragm	3.6W X-LED ³ system with adjustable intensity
B-293PLi	Trinocular, 360° rotating, 30° inclined.	Wide Field 10x/20mm	Quadruple, reversed	IOS E-PLAN 4x, 10x, 40x, 100x	Double layer, 150x139 mm with X-Y moving range 75x33mm. Rackless in X direction	Coaxial coarse and fine focusing	Sliding-in, N.A. 1.25 Abbe type with adjustable height and iris diaphragm	3.6W X-LED ³ system with adjustable intensity
B-290TB	Binocular, 360° rotating, 30° inclined.	Wide Field 10x/20mm	Quadruple, reversed	E-PLAN 4x, 10x, 40x, 100x	Double layer, 150x139 mm with X-Y moving range 75x33mm. Rackless in X direction	Coaxial coarse and fine focusing	Sliding-in, N.A. 1.25 Abbe type with adjustable height and iris diaphragm	3.6W X-LED ³ system with adjustable intensity

B-290 Series - Zoom comparison



Ascaris female - B-292 - 4x objective



Ascaris female - B-292 - 10x objective



Ascaris female - B-292 - 40x objective



X-LED³ advantages over halogen illumination

- Improved colour fidelity
- Pure white colour temperature
- Brighter images
- Incredibly low energy consumptions
- Longer lifespan

B-290 Series – Accessories

ACCESSORIES FOR B-290 SERIES

M-160	Eyepiece WF10x/20mm.
M-161	Eyepiece WF15x/16mm.
M-162	Eyepiece WF20x/10mm.
M-163	Micrometer eyepiece WF10x/20mm, 10mm/100um.
M-008.1	Eyepiece with pointer WF10x/20mm.
M-164	E-PLAN objective 4x/0.10 (only for B-292 / B-293 / B-290TB).
M-165	E-PLAN objective 10x/0.25 (only for B-292 / B-293 / B-290TB).
M-166	E-PLAN objective 20x/0.40 (only for B-292 / B-293 / B-290TB).
M-167	E-PLAN objective 40x/0.65 (only for B-292 / B-293 / B-290TB).
M-168	E-PLAN objective 60x/0.80 (only for B-292 / B-293 / B-290TB).
M-169	E-PLAN objective 100x/1.25 (Oil) (only for B-292 / B-293 / B-290TB).
M-144	IOS E-PLAN objective 4x/0.10 (only for B-292PLi / B-293PLi).
M-145	IOS E-PLAN objective 10x/0.25 (only for B-292PLi / B-293PLi).
M-146	IOS E-PLAN objective 20x/0.40 (only for B-292PLi / B-293PLi).
M-147	IOS E-PLAN objective 40x/0.65 (only for B-292PLi / B-293PLi).
M-148	IOS E-PLAN objective 100x/1.25 (Oil) (only for B-292PLi / B-293PLi).
M-149	IOS E-PLAN objective 60x/0.80 (only for B-292PLi / B-293PLi).
M-174	Polarizing set, filters only (for B-290 series).
M-184	Darkfield condenser.
M-175	Rotating table for polarizing set.
M-069	Solar battery pack.
M-971	Plane-concave mirror, with base.
M-114	C-Mount adapter for 1/2" sensor.
M-115	C-Mount adapter for 1/3" sensor.
M-116	C-Mount adapter for 2/3" sensor.
M-173	Photo adapter for APS-C and Full Frame Reflex cameras.
M-975	Blue filter, 45mm diameter.
M-977	Green filter, 45mm diameter.
M-979	Yellow filter, 45mm diameter.
M-989	Frosted glass filter, 45mm diameter.
M-666.290	Heating stage, with digital temperature controller.
M-005	Micrometer slide for software calibration, 1mm/10um, 10mm/100um.
M-031.1	Plastic dust cover – For 290 Series.
M-031.3	TNT dust cover – For B-290TB.
15008	OPTIKA immersion oil 10ml.
15104	Cleaning kit.
VP-290	IQ/OQ/PQ Validation Protocols.

M-069 - Solar battery pack

Included battery: rechargeable – Lithium-Poly. Capacity: 2600 mAh.
Output voltage: 5.5Vdc. - Dimensions: 120x73x10 mm.
Autonomy: over 6 hours at medium intensity (X-LED³).
Charging modes: with solar panel (12h),
with external USB power supply (not included)
or from PC USB port (5h).



15104 - Cleaning kit

It cleans glass quickly and effectively,
without leaving residue or odor.
Ideal for precision lens or prism cleaning.



How to connect the cameras to our microscopes.

Please refer to the Adapter reference list on Digital section.

Headquarters and Manufacturing Facilities

OPTIKA® S.r.l.

Via Rigla, 30 - 24010 Ponteranica (BG) - ITALIA - Tel.: +39 035.571.392 - Fax: +39 035.571.435 - info@optikamicroscopes.com

Optika Sales branches

OPTIKA® Spain

spain@optikamicroscopes.com

OPTIKA® China

china@optikamicroscopes.com

OPTIKA® India

india@optikamicroscopes.com

OPTIKA® USA

usa@optikamicroscopes.com

OPTIKA® Hungary

hungary@optikamicroscopes.com